


DRUM HEATERS

Hotco Pty Ltd

These units provide uniform low heat for relatively low melting-point solids or increasing the 'flowability' of thick viscous fluids such as molasses, grease, oils, fats, adhesives, chemicals, and paints etc., to facilitate easy and economical removal from storage containers.

The following pages illustrate the varied range of Hotco drum heaters available, consult with Hotco for selection and application.



FLEXIBLE SILICONE RUBBER DRUM HEATERS - Type 8 <!)) &' \$HGž8 <!) &' \$HG

These drum heaters are constructed from silicone rubber, reinforced with fibreglass sheet and incorporated in an earthed metal screen. They are 100 mm (4") wide and come complete with 1.2 m (48") flex.

Being a moulded assembly they are liquid resistant and extremely flexible to fit snugly around the drum with a simple spring attachment ensuring good contact.

CATALOGUE NUMBER	WATTAGE	VOLTAGE	DRUM SIZE
DH-55230TS	1000	240	200 L / 44 GAL
DH-5230TS	300	240	20 L / 5 GAL

CLAMP-ON METAL BAND - Type 8 A!((HG and 8 A!&\$HG

These very portable units are a semi-flexible clamp-on metal band and are applied to the outer diameter of the drum by means of adjustable spring loaded clamps.

The units are 127mm (5" wide) and applied heat at the area of contact is 10kW/m² (6.6w/in²) and are controlled by a thermostat (1 0° to H30°) with H&[!^ÁÐ àà^!Á æáá áÁ!á á Á!~ Á~]] á á! [•^È

CATALOGUE NUMBER	WATTAGE	VOLTAGE	DRUM SIZE
DM-44TS	2400	240	200 L / 44 GAL
DM-20TS	750	240	20 L / 5 GAL

If extra heat is required for a faster heating period, installation of a second band on the drum is advisable.


BASE DRUM HEATER - Type 8 A6' %), and HBD2

HOTCO base drum heaters are manufactured with the element cast into a heavy section base plate, resulting in an extremely robust and reliable drum heater. Temperature is thermostatically controlled and provision is made for permanent floor fixing.

CATALOGUE NUMBER	WATTAGE	VOLTAGE	DRUM SIZE
DMB-3158	2400	240	200 L / 44 GAL
HBD2	750	240	20 L / 5 GAL

ALL THE ABOVE ARE AVAILABLE EX STOCK

DRUM HEATERS



**FLEXIBLE
SILICONE
RUBBER DRUM
HEATER
240V 1000W
DH55230TS**


**CLAMP-ON
METAL BAND
DRUM HEATER
240V 2400W
DM44TS**

**BASE DRUM
HEATER
240V 2400W
DMB3158**

DRUM HEATERS

HOTCO DRUM HEATING OVENS


Designed for applications where many drums require heating or storing at a controlled temperature. Constructed using steel skinned insulated panels, HOTCO drum ovens feature a fan forced recirculated air system, 7 day 24 hour time control and adjustable thermostat.



NOTE

The range of HOTCO standard drum ovens (table below) have a maximum temperature rating of 70°C for continuous operation. For higher operational temperatures please consult with HOTCO and discuss your particular requirements.

CATALOGUE NUMBER	EXTERNAL WIDTH	EXTERNAL DEPTH	EXTERNAL HEIGHT	DOOR CONFIGURATION	KW INCLUDING FAN
DH01 (4 DRUM)	1682MM	1600MM	1743MM	2 X FRONT OPENING	12KW
DH02H (8 DRUM)	3352MM	1600MM	1743MM	4 X FRONT OPENING	18KW
DH02V (8 DRUM)	1682MM	1600MM	2993MM	2 X FRONT OPENING	18KW



HOTCO HEATED DRUM RACK

The heated drum rack is designed to facilitate easy loading, transport and dispensing from 200 litre drums.

Used where materials such as grases, fat, resin, waxes and tallow require heat to create a flow.

Controlled with an energy regulator, the heated drum rack is rated 240 volt 2400 watts enabling connection to a 10 amp 24 hour programmable timer if desired.



HOTCO DRUM IMMERSION HEATER

Designed for open top drum applications, the drum immersion heater is fitted with a unique depth regulating device, offering the economy of heating or melting only the portion of the contents required. Used where materials such as grease, fat, wax and tallow require heat to create a flow. This robust heater is rated 240 volt 2400 watt enabling connection to a 10 amp programmable timer if desired. For product suitability consult with HOTCO.

Watt density 30 kW/m² (20 watt/in²)